



1.56普通球面镜片参数表

1.56 SPH LENS SPECIFICATION

编号: SWPS-FSV-001 版本: 1

前弯	后弯	中心厚度	边缘厚度	球光 (-/+)	前弯	后弯	中心厚度	边缘厚度
FRONT CURVE	BACK CURVE	CT (mm)	ET (mm)	SPH (-/+)	FRONT CURVE	BACK CURVE	CT (mm)	ET (mm)
4.00	4.00	2.0	2.2	0.00				
3.75	4.00	1.7	2.0	0.25	4.25	4.00	1.8	1.6
3.50	4.00	1.5	2.2	0.50	4.50	4.00	1.9	1.4
3.25	4.00	1.5	2.5	0.75	4.75	4.00	2.1	1.4
3.00	4.00	1.5	2.8	1.00	5.00	4.00	2.4	1.4
2.75	4.00	1.3	2.9	1.25	4.25	3.00	2.4	1.2
2.50	4.00	1.3	3.2	1.50	4.50	3.00	2.7	1.2
3.25	5.00	1.3	3.6	1.75	4.75	3.00	2.9	1.2
3.00	5.00	1.3	3.9	2.00	5.00	3.00	3.2	1.2
2.75	5.00	1.3	4.3	2.25	4.25	2.00	3.4	1.2
2.50	5.00	1.3	4.5	2.50	4.50	2.00	3.6	1.2
2.25	5.00	1.3	4.8	2.75	4.75	2.00	4.0	1.2
2.00	5.00	1.3	5.0	3.00	5.00	2.00	4.0	1.2
2.75	6.00	1.3	5.6	3.25	5.25	2.00	4.4	1.2
2.50	6.00	1.3	5.9	3.50	5.50	2.00	4.7	1.2
2.25	6.00	1.3	6.2	3.75	5.75	2.00	4.9	1.2
2.00	6.00	1.3	6.6	4.00	6.00	2.00	5.2	1.2

CYL (-)									SPH (-/+)	CYL (-)								
2.00	1.75	1.50	1.25	1.00	0.75	0.50	0.25	0.00		0.00	0.25	0.50	0.75	1.00	1.25	1.50	1.75	2.00
									0.00									
									0.25									
									0.50									
									0.75									
									1.00									
									1.25									
									1.50									
									1.75									
									2.00									
									2.25									
									2.50									
									2.75									
									3.00									
									3.25									
									3.50									
									3.75									
									4.00									

72mm

65mm

1.75	6.00	1.3	6.9	4.25	6.25	2.00	5.4	1.2
1.50	6.00	1.3	7.2	4.50	6.50	2.00	5.6	1.2
2.25	7.00	1.3	7.8	4.75	6.75	2.00	5.9	1.2
2.00	7.00	1.3	7.9	5.00	7.00	2.00	6.2	1.2
1.75	7.00	1.3	8.3	5.25	6.25	1.00	6.3	1.2
1.50	7.00	1.3	8.6	5.50	6.50	1.00	6.5	1.2
1.25	7.00	1.3	9.0	5.75	6.75	1.00	6.7	1.2
1.00	7.00	1.3	9.2	6.00	7.00	1.00	7.1	1.2
2.75	9.00	1.3	9.2	6.25				
2.50	9.00	1.3	9.6	6.50				
2.25	9.00	1.3	9.8	6.75				
2.00	9.00	1.3	10.2	7.00				
1.75	9.00	1.3	10.4	7.25				
1.50	9.00	1.3	10.6	7.50				
1.25	9.00	1.3	11.1	7.75				
1.00	9.00	1.3	11.3	8.00				

							4.25							
							4.50							
							4.75							
							5.00							
							5.25							
							5.50							
							5.75							
							6.00							
							6.25							
							6.50							
							6.75							
							7.00							
							7.25							
							7.50							
							7.75							
							8.00							

70mm

适用于Apply to	本产品
中心厚度允差C.T. Tolerance	±0.3mm
边缘厚度允差E.T. Tolerance	±0.3mm最低不低于1.0mm
直径允差Diameter Tolerance	-0.5mm
设计DESIGN	球面
材料折射率MATERIAL INDEX	1.550
阿贝数ABBE VALUE	35.0
比重SPECIFIC GRAVITY	1.28

透射比分类	0类
-------	----

编写人/日期 WRITTEN BY / DATE	审核人/日期 VERIFIED BY /DATE	批准人/日期 APPROVED BY /DATE

保密 ©视悦光学有限公司
仅供内部使用 - 请勿泄露、复制或传播



1.56普通球面高散镜片参数表

1.56 SPH HI CYL LENS SPECIFICATION

编号：SWPS-FSV-001-01 版本：1

前弯	后弯	中心厚度	高散边缘厚度	球光 (-/+)	前弯	后弯	高散中心厚度	边缘厚度
FRONT CURVE	BACK CURVE	CT (mm)	ET (mm)	SPH (-/+)	FRONT CURVE	BACK CURVE	CT (mm)	ET (mm)
4.00	4.00	2.0	2.2	0.00				
3.75	4.00	1.7	2.2	0.25	4.25	4.00	1.7	1.6
3.50	4.00	1.5	2.3	0.50	4.50	4.00	1.8	1.4
3.25	4.00	1.5	2.6	0.75	4.75	4.00	2.0	1.4
3.00	4.00	1.5	2.8	1.00	5.00	4.00	2.3	1.4
2.75	4.00	1.3	2.9	1.25	4.25	3.00	2.3	1.2
2.50	4.00	1.3	3.3	1.50	4.50	3.00	2.6	1.2
3.25	5.00	1.3	3.6	1.75	4.75	3.00	2.8	1.2
3.00	5.00	1.3	4.0	2.00	5.00	3.00	3.1	1.2
2.75	5.00	1.3	4.2	2.25	4.25	2.00	3.4	1.2
2.50	5.00	1.3	4.5	2.50	4.50	2.00	3.6	1.2
2.25	5.00	1.3	4.6	2.75	4.75	2.00	3.9	1.2

CYL (-)								SPH (-/+)	CYL (-)							
4.00	3.75	3.50	3.25	3.00	2.75	2.50	2.25		2.25	2.50	2.75	3.00	3.25	3.50	3.75	4.00
								0.00								
								0.25								
								0.50								
								0.75								
								1.00								
								1.25								
								1.50								
								1.75								
								2.00								
								2.25								
								2.50								
								2.75								

70mm

2.00	5.00	1.3	4.9	3.00	5.00	2.00	4.2	1.2
2.75	6.00	1.3	5.6	3.25	5.25	2.00	4.3	1.2
2.50	6.00	1.3	5.9	3.50	5.50	2.00	4.6	1.2
2.25	6.00	1.3	6.2	3.75	5.75	2.00	4.8	1.2
2.00	6.00	1.3	6.4	4.00	6.00	2.00	5.1	1.2
1.75	6.00	1.3	6.7	4.25	6.25	2.00	5.3	1.2
1.50	6.00	1.3	7.2	4.50	6.50	2.00	5.6	1.2
2.25	7.00	1.3	7.4	4.75	6.75	2.00	5.9	1.2
2.00	7.00	1.3	7.9	5.00	7.00	2.00	6.1	1.2
1.75	7.00	1.3	8.2	5.25	6.25	1.00	6.3	1.2
1.50	7.00	1.3	8.5	5.50	6.50	1.00	6.5	1.2
1.25	7.00	1.3	8.6	5.75	6.75	1.00	6.7	1.2
1.00	7.00	1.3	8.9	6.00	7.00	1.00	7.0	1.2
2.75	9.00	1.3	9.5	6.25				
2.50	9.00	1.3	9.8	6.50				
2.25	9.00	1.3	10.2	6.75				
2.00	9.00	1.3	10.2	7.00				
1.75	9.00	1.3	10.5	7.25				
1.50	9.00	1.3	10.8	7.50				
1.25	9.00	1.3	11.2	7.75				
1.00	9.00	1.3	11.4	8.00				

								3.00									65mm			
								3.25												
								3.50												
								3.75												
								4.00												
								4.25												
								4.50												
								4.75												
								5.00												
								5.25												
								5.50												
								5.75												
								6.00												
								6.25												
								6.50												
								6.75												
								7.00												
								7.25												
								7.50												
								7.75												
								8.00												

适用于Apply to	本产品
中心厚度允差C. T. Tolerance	±0.3mm
边缘厚度允差E. T. Tolerance	±0.3mm最低不低于1.0mm
直径允差Diameter Tolerance	-0.5mm
设计DESIGN	球面
材料折射率MATERIAL INDEX	1.550
阿贝数ABBE VALUE	35.0
比重SPECIFIC GRAVITY	1.28
透射比分类	0类

编写人/日期 WRITTEN BY / DATE	审核人/日期 VERIFIED BY /DATE	批准人/日期 APPROVED BY /DATE

保密 ©视悦光学有限公司
仅供内部使用 - 请勿泄露、复制或传播

[返回](#)

