



1.56 2号抗蓝光非球面镜片参数表

1.56 BLUE FILTER PRO ASP LENS SPECIFICATION

编号: SWPS-FSV-039 版本: 2

| 前弯 | 后弯 | 中心厚度 | 边缘厚度 | 球光 (-/+) | 前弯 | 后弯 | 中心厚度 | 边缘厚度 |
|-------------|------------|---------|---------|-----------|-------------|------------|---------|---------|
| FRONT CURVE | BACK CURVE | CT (mm) | ET (mm) | SPH (-/+) | FRONT CURVE | BACK CURVE | CT (mm) | ET (mm) |
| 3.00 | 3.00 | 2.0 | 2.2 | 0.00 | | | | |
| 2.75 | 3.00 | 1.9 | 2.3 | 0.25 | 3.25 | 3.00 | 1.8 | 1.5 |
| 2.50 | 3.00 | 1.8 | 2.5 | 0.50 | 3.50 | 3.00 | 2.1 | 1.6 |
| 2.25 | 3.00 | 1.7 | 2.7 | 0.75 | 3.75 | 3.00 | 2.0 | 1.4 |
| 2.00 | 3.00 | 1.6 | 2.9 | 1.00 | 4.00 | 3.00 | 2.3 | 1.4 |
| 1.75 | 3.00 | 1.5 | 3.1 | 1.25 | 4.25 | 3.00 | 2.4 | 1.3 |
| 3.00 | 4.50 | 1.4 | 3.2 | 1.50 | 4.50 | 3.00 | 2.7 | 1.4 |
| 2.75 | 4.50 | 1.2 | 3.3 | 1.75 | 4.75 | 3.00 | 2.8 | 1.1 |
| 2.50 | 4.50 | 1.2 | 3.7 | 2.00 | 5.00 | 3.00 | 3.2 | 1.4 |
| 2.25 | 4.50 | 1.2 | 4.0 | 2.25 | 4.25 | 2.00 | 3.1 | 1.1 |
| 2.00 | 4.50 | 1.2 | 4.3 | 2.50 | 4.50 | 2.00 | 3.3 | 1.0 |
| 1.75 | 4.50 | 1.2 | 4.6 | 2.75 | 4.75 | 2.00 | 3.7 | 1.1 |
| 1.50 | 4.50 | 1.2 | 5.0 | 3.00 | 5.00 | 2.00 | 4.0 | 1.2 |
| 1.25 | 4.50 | 1.2 | 5.2 | 3.25 | 5.25 | 2.00 | 4.1 | 1.1 |
| 1.00 | 4.50 | 1.2 | 5.5 | 3.50 | 5.50 | 2.00 | 4.3 | 1.1 |
| 0.75 | 4.50 | 1.2 | 5.8 | 3.75 | 5.75 | 2.00 | 4.6 | 1.1 |
| 0.50 | 4.50 | 1.2 | 6.1 | 4.00 | 6.00 | 2.00 | 4.7 | 1.1 |
| 1.25 | 5.50 | 1.2 | 6.4 | 4.25 | 5.25 | 1.00 | 4.9 | 1.1 |
| 1.00 | 5.50 | 1.2 | 6.7 | 4.50 | 5.50 | 1.00 | 5.2 | 1.1 |
| 0.75 | 5.50 | 1.2 | 7.0 | 4.75 | 5.75 | 1.00 | 5.4 | 1.1 |
| 0.50 | 5.50 | 1.2 | 7.2 | 5.00 | 6.00 | 1.00 | 5.7 | 1.2 |
| 1.25 | 6.50 | 1.2 | 7.6 | 5.25 | 6.25 | 1.00 | 5.9 | 1.2 |
| 1.00 | 6.50 | 1.2 | 8.1 | 5.50 | 6.50 | 1.00 | 6.1 | 1.1 |
| 0.75 | 6.50 | 1.2 | 8.3 | 5.75 | 6.75 | 1.00 | 6.4 | 1.1 |
| 0.50 | 6.50 | 1.2 | 8.6 | 6.00 | 7.00 | 1.00 | 6.6 | 1.1 |
| 1.25 | 7.50 | 1.2 | 8.6 | 6.25 | | | | |
| 1.00 | 7.50 | 1.2 | 8.9 | 6.50 | | | | |
| 0.75 | 7.50 | 1.2 | 9.3 | 6.75 | | | | |
| 0.50 | 7.50 | 1.2 | 9.3 | 7.00 | | | | |
| 1.25 | 8.50 | 1.2 | 10.1 | 7.25 | | | | |
| 1.00 | 8.50 | 1.2 | 10.3 | 7.50 | | | | |
| 0.75 | 8.50 | 1.2 | 10.6 | 7.75 | | | | |
| 0.50 | 8.50 | 1.2 | 10.7 | 8.00 | | | | |

| CYL(-) | | | | | | | | SPH (-/+) | CYL(-) | | | | | | | | | |
|--------|------|------|------|------|------|------|------|-----------|--------|------|------|------|------|------|------|------|------|------|
| 2.00 | 1.75 | 1.50 | 1.25 | 1.00 | 0.75 | 0.50 | 0.25 | | 0.00 | 0.00 | 0.25 | 0.50 | 0.75 | 1.00 | 1.25 | 1.50 | 1.75 | 2.00 |
| | | | | | | | | 0.00 | | | | | | | | | | |
| | | | | | | | | 0.25 | | | | | | | | | | |
| | | | | | | | | 0.50 | | | | | | | | | | |
| | | | | | | | | 0.75 | | | | | | | | | | |
| | | | | | | | | 1.00 | | | | | | | | | | |
| | | | | | | | | 1.25 | | | | | | | | | | |
| | | | | | | | | 1.50 | | | | | | | | | | |
| | | | | | | | | 1.75 | | | | | | | | | | |
| | | | | | | | | 2.00 | | | | | | | | | | |
| | | | | | | | | 2.25 | | | | | | | | | | |
| | | | | | | | | 2.50 | | | | | | | | | | |
| | | | | | | | | 2.75 | | | | | | | | | | |
| | | | | | | | | 3.00 | | | | | | | | | | |
| | | | | | | | | 3.25 | | | | | | | | | | |
| | | | | | | | | 3.50 | | | | | | | | | | |
| | | | | | | | | 3.75 | | | | | | | | | | |
| | | | | | | | | 4.00 | | | | | | | | | | |
| | | | | | | | | 4.25 | | | | | | | | | | |
| | | | | | | | | 4.50 | | | | | | | | | | |
| | | | | | | | | 4.75 | | | | | | | | | | |
| | | | | | | | | 5.00 | | | | | | | | | | |
| | | | | | | | | 5.25 | | | | | | | | | | |
| | | | | | | | | 5.50 | | | | | | | | | | |
| | | | | | | | | 5.75 | | | | | | | | | | |
| | | | | | | | | 6.00 | | | | | | | | | | |
| | | | | | | | | 6.25 | | | | | | | | | | |
| | | | | | | | | 6.50 | | | | | | | | | | |
| | | | | | | | | 6.75 | | | | | | | | | | |
| | | | | | | | | 7.00 | | | | | | | | | | |
| | | | | | | | | 7.25 | | | | | | | | | | |
| | | | | | | | | 7.50 | | | | | | | | | | |
| | | | | | | | | 7.75 | | | | | | | | | | |
| | | | | | | | | 8.00 | | | | | | | | | | |

| | |
|------------------------|-----------------|
| 适用于Apply to | 本产品 |
| 中心厚度公差C.T. Tolerance | ±0.3mm 不低于1.0mm |
| 边缘厚度公差E.T. Tolerance | ±0.3mm |
| 直径公差Diameter Tolerance | -0.5mm |
| 设计DESIGN | 非球面 |
| 材料折射率MATERIAL INDEX | 1.551 |
| 阿贝数ABBE VALUE | 39.1 |
| 比重SPECIFIC GRAVITY | 1.28 |
| 透射比分类 | 0类 |

| | | |
|-----------------------------|------------------------------|------------------------------|
| 编写人/日期 WRITTEN BY / DATE | 审核人/日期 VERIFIED BY / DATE | 批准人/日期 APPROVED BY / DATE |
| | | |