



1.56快变渐进多焦点 (C-9mm) 镜片参数表 (180轴位)

1.56 FAST CHANGE PROGRESSIVE (C-9mm) LENS SPECIFICATION 180

编号: SWPS-FSV-045 版本: 1

| 前弯 | 后弯 | 中心厚度 | 边缘厚度 | 球光 (-/+) | 前弯 | 后弯 | 中心厚度 | 边缘厚度 |
|-------------|------------|---------|---------|-------------|-------------|------------|---------|---------|
| FRONT CURVE | BACK CURVE | CT (mm) | ET (mm) | SPH (-/+) | FRONT CURVE | BACK CURVE | CT (mm) | ET (mm) |
| | | | | 0.00 | 3.50 | 3.50 | — | 2.0 |
| 3.50 | 3.75 | 2.4 | | 0.25 | 3.50 | 3.25 | — | 2.0 |
| 3.50 | 4.00 | 2.3 | | 0.50 | 3.50 | 3.00 | — | 2.0 |
| 3.50 | 4.25 | 2.0 | | 0.75 | 3.50 | 2.75 | — | 1.8 |
| 3.50 | 4.50 | 2.0 | | 1.00 | 3.50 | 2.50 | — | 1.8 |
| 3.50 | 4.75 | 2.0 | | 1.25 | 3.50 | 2.25 | — | 1.5 |
| 3.50 | 5.00 | 2.0 | | 1.50 | 3.50 | 2.00 | — | 1.5 |
| 3.50 | 5.25 | 2.0 | | 1.75 | 3.50 | 1.75 | — | 1.5 |
| 3.50 | 5.50 | 2.0 | | 2.00 | 3.50 | 1.50 | — | 1.5 |
| 3.50 | 5.75 | 2.0 | | 2.25 | 3.50 | 1.25 | — | 1.5 |
| 3.50 | 6.00 | 2.0 | | 2.50 | 3.50 | 1.00 | — | 1.5 |
| 3.50 | 6.25 | 2.0 | | 2.75 | 3.50 | 0.75 | — | 1.5 |
| 3.50 | 6.50 | 2.0 | | 3.00 | 3.50 | 0.50 | — | 1.5 |

| ADD 9mm1.00~3.00(L/R) | | | | | | | | SPH (-/+) | ADD 9mm1.00~3.00(L/R) | | | | | | | | |
|-----------------------|------|------|------|------|------|------|------|-----------|-----------------------|------|------|------|------|------|------|------|------|
| 3.00 | 2.75 | 2.50 | 2.25 | 2.00 | 1.75 | 1.50 | 1.25 | | 1.00 | 1.25 | 1.50 | 1.75 | 2.00 | 2.25 | 2.50 | 2.75 | 3.00 |
| CYL (-) | | | | | | | | | CYL (-) | | | | | | | | |
| | | | | | | | | 0.00 | | | | | | | | | |
| | | | | | | | | 0.25 | | | | | | | | | |
| | | | | | | | | 0.50 | | | | | | | | | |
| | | | | | | | | 0.75 | | | | | | | | | |
| | | | | | | | | 1.00 | | | | | | | | | |
| | | | | | | | | 1.25 | | | | | | | | | |
| | | | | | | | | 1.50 | | | | | | | | | |
| | | | | | | | | 1.75 | | | | | | | | | |
| | | | | | | | | 2.00 | | | | | | | | | |
| | | | | | | | | 2.25 | | | | | | | | | |
| | | | | | | | | 2.50 | | | | | | | | | |
| | | | | | | | | 2.75 | | | | | | | | | |
| | | | | | | | | 3.00 | | | | | | | | | |

| | |
|------------------------|-------------------|
| 适用于Apply to | 快变灰 |
| 中心厚度允差C.T. Tolerance | ± 0.3mm |
| 边缘厚度允差E.T. Tolerance | ± 0.3mm |
| 直径允差Diameter Tolerance | -0.5mm |
| 设计DESIGN | 渐进 |
| 材料折射率MATERIAL INDEX | 1.550 |
| 阿贝数ABBE VALUE | 40.0 |
| 比重SPECIFIC GRAVITY | 1.28 |
| 透射比分类 | 0类 (变色前) 2类 (变色后) |

| 编写人/日期 WRITTEN BY / DATE | 审核人/日期 VERIFIED BY / DATE | 批准人/日期 APPROVED BY / DATE |
|-----------------------------|------------------------------|------------------------------|
| | | |

保密 © 视悦光学有限公司
 仅供内部使用 - 请勿泄露、复制或传播