



1.60变色非球面镜片参数表

1.60 PHOTOCROMIC ASP LENS SPECIFICATION

编号: SWPS-FSV-052 版本: 2

前弯	后弯	中心厚度	边缘厚度	球光 (-/+)	前弯	后弯	中心厚度	边缘厚度
FRONT CURVE	BACK CURVE	CT (mm)	ET (mm)	SPH (-/+)	FRONT CURVE	BACK CURVE	CT (mm)	ET (mm)
3.50	3.50	2.0	—	0.00				
3.25	3.50	2.0	—	0.25	3.25	3.00	—	2.0
3.00	3.50	2.0	—	0.50	3.50	3.00	—	2.0
2.75	3.50	2.0	—	0.75	3.75	3.00	—	1.8
2.50	3.50	2.0	—	1.00	4.00	3.00	—	1.8
2.75	4.00	2.0	—	1.25	4.25	3.00	—	1.5
2.50	4.00	2.0	—	1.50	4.50	3.00	—	1.5
2.25	4.00	2.0	—	1.75	4.75	3.00	—	1.5
2.00	4.00	2.0	—	2.00	5.00	3.00	—	1.5
2.25	4.50	2.0	—	2.25	4.25	2.00	—	1.5
2.00	4.50	2.0	—	2.50	4.50	2.00	—	1.5
1.75	4.50	2.0	—	2.75	4.75	2.00	—	1.5
1.50	4.50	2.0	—	3.00	5.00	2.00	—	1.5
2.25	5.50	2.0	—	3.25	5.25	2.00	—	1.5
2.00	5.50	2.0	—	3.50	5.50	2.00	—	1.5
1.75	5.50	2.0	—	3.75	5.75	2.00	—	1.5
1.50	5.50	2.0	—	4.00	6.00	2.00	—	1.5
1.75	6.00	2.0	—	4.25	6.25	2.00	—	1.2
1.50	6.00	2.0	—	4.50	6.50	2.00	—	1.2
1.25	6.00	2.0	—	4.75	6.75	2.00	—	1.2
1.00	6.00	2.0	—	5.00	7.00	2.00	—	1.2
1.25	6.50	2.0	—	5.25	6.25	1.00	—	1.2
1.00	6.50	2.0	—	5.50	6.50	1.00	—	1.2
0.75	6.50	2.0	—	5.75	6.75	1.00	—	1.2
0.50	6.50	2.0	—	6.00	7.00	1.00	—	1.2
1.25	7.50	2.0	—	6.25				
1.00	7.50	2.0	—	6.50				
0.75	7.50	2.0	—	6.75				
0.50	7.50	2.0	—	7.00				
1.25	8.50	2.0	—	7.25				
1.00	8.50	2.0	—	7.50				
0.75	8.50	2.0	—	7.75				
0.50	8.50	2.0	—	8.00				
1.25	9.50	2.0	—	8.25				
1.00	9.50	2.0	—	8.50				
0.75	9.50	2.0	—	8.75				
0.50	9.50	2.0	—	9.00				
1.25	10.50	2.0	—	9.25				
1.00	10.50	2.0	—	9.50				
0.75	10.50	2.0	—	9.75				
0.50	10.50	2.0	—	10.00				

CYL(-)												SPH (-/+)	CYL(-)															
4.00	3.50	3.25	3.00	2.75	2.50	2.25	2.00	1.75	1.50	1.25	1.00		0.00	0.25	0.50	0.75	1.00	1.25	1.50	1.75	2.00	2.25	2.50	2.75	3.00	3.25	3.50	4.00
													0.00															
													0.25															
													0.50															
													0.75															
													1.00															
													1.25															
													1.50															
													1.75															
													2.00															
													2.25															
													2.50															
													2.75															
													3.00															
													3.25															
													3.50															
													3.75															
													4.00															
													4.25															
													4.50															
													4.75															
													5.00															
													5.25															
													5.50															
													5.75															
													6.00															
													6.25															
													6.50															
													6.75															
													7.00															
													7.25															
													7.50															
													7.75															
													8.00															
													8.25															
													8.50															
													8.75															
													9.00															
													9.25															
													9.50															
													9.75															
													10.00															

适用于Apply to	本产品
中心厚度允差C.T. Tolerance	±0.3mm
边缘厚度允差E.T. Tolerance	±0.3mm
直径允差Diameter Tolerance	-0.5mm
设计DESIGN	非球面
材料折射率MATERIAL INDEX	1.603
阿贝数ABBE VALUE	30.0
比重SPECIFIC GRAVITY	1.35
透射比分类	

编写人/日期 WRITTEN BY / DATE	审核人/日期 VERIFIED BY /DATE	批准人/日期 APPROVED BY /DATE

保密 ©视悦光学有限公司
仅供内部使用 - 请勿泄露、复制或传播