



1.60 UV410非球面镜片参数表 1.60 UV410 ASP LENS SPECIFICATION

编号: SWPS-FSV-058 版本: 2

前弯	后弯	中心厚度	边缘厚度	球光 (-/+)	前弯	后弯	中心厚度	边缘厚度
FRONT CURVE	BACK CURVE	CT (mm)	ET (mm)	SPH (-/+)	FRONT CURVE	BACK CURVE	CT (mm)	ET (mm)
3.50	3.50	2.00	2.0	0.00				
3.25	3.50	1.50	1.9	0.25	3.75	3.50	1.6	1.5
3.00	3.50	1.50	2.2	0.50	4.00	3.50	1.8	1.5
2.75	3.50	1.50	2.5	0.75	4.25	3.50	2.0	1.5
2.50	3.50	1.50	2.8	1.00	4.50	3.50	2.3	1.5
2.75	4.00	1.15	2.6	1.25	4.75	3.50	2.1	1.1
2.50	4.00	1.15	2.9	1.50	5.00	3.50	2.3	1.1
2.25	4.00	1.15	3.1	1.75	5.25	3.50	2.5	1.1
2.00	4.00	1.15	3.4	2.00	5.50	3.50	2.7	1.1
2.25	4.50	1.15	3.9	2.25	4.65	2.40	2.9	1.1
2.00	4.50	1.15	4.1	2.50	4.90	2.40	3.1	1.1
1.75	4.50	1.15	4.2	2.75	5.15	2.40	3.3	1.1
1.50	4.50	1.15	4.5	3.00	5.40	2.40	3.5	1.1
2.25	5.50	1.15	5.0	3.25	5.65	2.40	3.7	1.1
2.00	5.50	1.15	5.2	3.50	5.90	2.40	3.9	1.1
1.75	5.50	1.15	5.5	3.75	6.15	2.40	4.1	1.1
1.50	5.50	1.15	6.0	4.00	6.40	2.40	4.3	1.1
1.75	6.00	1.15	6.2	4.25	6.65	2.40	4.5	1.1
1.50	6.00	1.15	6.4	4.50	6.90	2.40	4.7	1.1
1.25	6.00	1.15	6.6	4.75	7.15	2.40	4.9	1.1
1.00	6.00	1.15	6.9	5.00	7.40	2.40	5.1	1.1
1.25	6.50	1.15	7.3	5.25	7.15	1.90	5.3	1.1
1.00	6.50	1.15	7.5	5.50	7.40	1.90	5.5	1.1
0.75	6.50	1.15	7.8	5.75	7.65	1.90	5.6	1.1
0.50	6.50	1.15	8.1	6.00	7.90	1.90	5.8	1.1
1.25	7.50	1.15	7.5	6.25				
1.00	7.50	1.15	8.0	6.50				
0.75	7.50	1.15	8.2	6.75				
0.50	7.50	1.15	8.4	7.00				
1.25	8.50	1.15	9.0	7.25				
1.00	8.50	1.15	9.3	7.50				
0.75	8.50	1.15	9.5	7.75				
0.50	8.50	1.15	9.7	8.00				
1.25	9.50	1.15	10.1	8.25				
1.00	9.50	1.15	10.5	8.50				
0.75	9.50	1.15	10.7	8.75				
0.50	9.50	1.15	10.9	9.00				
1.25	10.50	1.15	11.6	9.25				
1.00	10.50	1.15	11.8	9.50				
0.75	10.50	1.15	12.1	9.75				
0.50	10.50	1.15	12.3	10.00				

CYL(-)												SPH (-/+)	CYL(-)																
4.00	3.75	3.50	3.25	3.00	2.75	2.50	2.25	2.00	1.75	1.50	1.25		0.00	0.25	0.50	0.75	1.00	1.25	1.50	1.75	2.00	2.25	2.50	2.75	3.00	3.25	3.50	3.75	4.00
													0.00																
													0.25																
													0.50																
													0.75																
													1.00																
													1.25																
													1.50																
													1.75																
													2.00																
													2.25																
													2.50																
													2.75																
													3.00																
													3.25																
													3.50																
													3.75																
													4.00																
													4.25																
													4.50																
													4.75																
													5.00																
													5.25																
													5.50																
													5.75																
													6.00																
													6.25																
													6.50																
													6.75																
													7.00																
													7.25																
													7.50																
													7.75																
													8.00																
													8.25																
													8.50																
													8.75																
													9.00																
													9.25																
													9.50																
													9.75																
													10.00																

适用于Apply to	本产品
中心厚度允差C.T. Tolerance	- 0.15mm +0.2mm (for CT 1.15) Other & PLUS; ± 0.2mm
边缘厚度允差E.T. Tolerance	± 0.3mm
直径允差Diameter Tolerance	-0.5mm
设计DESIGN	非球面
材料折射率MATERIAL INDEX	1.597
阿贝数ABBE VALUE	40.0
比重SPECIFIC GRAVITY	1.28
透射比分类	0类, UV-1

编写人/日期 WRITTEN BY / DATE	审核人/日期 VERIFIED BY / DATE	批准人/日期 APPROVED BY / DATE