



### 1.67 MR-7 UV410浅色舒缓镜片参数表

### 1.67 MR-7 UV410 LIGHT COLOR RELAX LENS SPECIFICATION

视悦光学

编号: SWPS-FSV-066 版本: 2

前弯	后弯	中心厚度	边缘厚度	球光 (-)
FRONT CURVE	BACK CURVE	CT (mm)	ET (mm)	SPH (-/+)
2.50	4.50	1.15	3.3	2.00
2.75	5.00	1.15	3.6	2.25
2.50	5.00	1.15	3.9	2.50
2.25	5.00	1.15	4.0	2.75
2.00	5.00	1.15	4.3	3.00
2.25	5.50	1.15	4.6	3.25
2.00	5.50	1.15	4.8	3.50
1.75	5.50	1.15	4.9	3.75
1.50	5.50	1.15	5.3	4.00
1.75	6.00	1.15	5.6	4.25
1.50	6.00	1.15	5.9	4.50
1.25	6.00	1.15	6.0	4.75
1.00	6.00	1.15	6.1	5.00
1.25	6.50	1.15	6.6	5.25
1.00	6.50	1.15	6.8	5.50
0.75	6.50	1.15	7.1	5.75
0.50	6.50	1.15	7.3	6.00
1.00	7.25	1.15	7.0	6.25
0.75	7.25	1.15	7.2	6.50
0.50	7.25	1.15	7.4	6.75
0.25	7.25	1.15	7.6	7.00
1.00	8.25	1.15	8.0	7.25
0.75	8.25	1.15	8.2	7.50
0.50	8.25	1.15	8.5	7.75
0.25	8.25	1.15	8.7	8.00

ADD(L/R)	SPH (-)
000	2.00
	2.25
	2.50
	2.75
	3.00
	3.25
	3.50
	3.75
	4.00
	4.25
75mm	4.50
	4.75
	5.00
	5.25
	5.50
	5.75
	6.00
	6.25
	6.50
	6.75
70mm	7.00
	7.25
	7.50
	7.75
	8.00

适用于 Apply to	适用于本产品
中心厚度允差C.T. Tolerance	-0.15mm +0.2mm
边缘厚度允差E.T. Tolerance	± 0.3mm
直径允差Diameter Tolerance	-0.5mm
设计DESIGN	渐进
材料折射率MATERIAL INDEX	1.665
阿贝数ABBE VALUE	32.0
比重SPECIFIC GRAVITY	1.34
透射比分类	0类, UV-1

编写人/日期 WRITTEN BY / DATE	审核人/日期 VERIFIED BY / DATE	准人/日期 APPROVED BY / DATE