



1.74 非球面镜片参数表  
1.74 ASP LENS SPECIFICATION

编号: SWPS-FSV-067 版本: 1

前弯	后弯	中心厚度	边缘厚度	球光 (-/+)	前弯	后弯	中心厚度	边缘厚度
FRONT CURVE	BACK CURVE	CT (mm)	ET (mm)	SPH (-/+)	FRONT CURVE	BACK CURVE	CT (mm)	ET (mm)
3.50	4.50	1.40	2.3	1.00				
3.25	4.50	1.30	2.4	1.25				
3.00	4.50	1.20	2.6	1.50				
2.75	4.50	1.20	2.8	1.75				
3.00	5.00	1.10	3.0	2.00				
2.75	5.00	1.10	3.3	2.25				
2.50	5.00	1.10	3.5	2.50				
2.25	5.00	1.10	3.8	2.75				
2.00	5.00	1.10	4.0	3.00	5.50	2.50	3.4	1.1
2.25	5.50	1.10	4.3	3.25	5.75	2.50	3.6	1.1
2.00	5.50	1.10	4.5	3.50	6.00	2.50	3.8	1.1
1.75	5.50	1.10	4.7	3.75	6.25	2.50	4.0	1.1
1.50	5.50	1.10	4.9	4.00	6.50	2.50	4.2	1.1
1.75	6.00	1.10	5.1	4.25	5.75	1.50	3.9	1.1
1.50	6.00	1.10	5.4	4.50	6.00	1.50	4.2	1.1
1.25	6.00	1.10	5.7	4.75	6.25	1.50	4.4	1.1
1.00	6.00	1.10	5.8	5.00	6.50	1.50	4.5	1.1
1.50	6.75	1.10	6.2	5.25	6.75	1.50	4.7	1.1
1.25	6.75	1.10	6.4	5.50	7.00	1.50	4.8	1.1
1.00	6.75	1.10	6.5	5.75	7.25	1.50	5.0	1.1
0.75	6.75	1.10	6.8	6.00	7.50	1.50	5.2	1.1
1.25	7.50	1.10	6.4	6.25				
1.00	7.50	1.10	6.6	6.50				
0.75	7.50	1.10	6.8	6.75				
1.25	8.25	1.10	7.1	7.00				
1.00	8.25	1.10	7.2	7.25				
0.75	8.25	1.10	7.4	7.50				
0.50	8.25	1.10	7.7	7.75				
0.25	8.25	1.10	7.9	8.00				
1.00	9.25	1.10	8.3	8.25				
0.75	9.25	1.10	8.4	8.50				
0.50	9.25	1.10	8.7	8.75				
0.25	9.25	1.10	8.8	9.00				
1.00	10.25	1.10	9.1	9.25				
0.75	10.25	1.10	9.3	9.50				
0.50	10.25	1.10	9.6	9.75				
0.25	10.25	1.10	9.7	10.00				
1.00	11.25	1.10	10.2	10.25				
0.75	11.25	1.10	10.4	10.50				
0.50	11.25	1.10	10.7	10.75				
0.25	11.25	1.10	10.9	11.00				
1.00	12.25	1.10	11.1	11.25				
0.75	12.25	1.10	11.3	11.50				
0.50	12.25	1.10	11.5	11.75				
0.25	12.25	1.10	11.6	12.00				
1.00	13.25	1.10	12.4	12.25				
0.75	13.25	1.10	12.5	12.50				
0.50	13.25	1.10	12.8	12.75				
0.25	13.25	1.10	12.8	13.00				
1.00	14.50	1.10	13.7	13.50				
0.50	14.50	1.10	14.2	14.00				
1.00	15.50	1.10	14.9	14.50				
0.50	15.50	1.10	15.5	15.00				

CYL(-)											SPH (-/+)	CYL(+)							
4.00	3.75	3.50	3.25	3.00	2.75	2.50	2.25	2.00	1.75	1.50		1.25	1.00	0.75	0.50	0.25	0.00		
																	1.00		
																	1.25		
																	1.50		
																	1.75		
																	2.00		
																	2.25		
																	2.50		
																	2.75		
																	3.00		
																	3.25		
																	3.50		
																	3.75		
																	4.00		
																	4.25		
																	4.50		
																	4.75		
																	5.00		
																	5.25		
																	5.50		
																	5.75		
																	6.00		
																	6.25		
																	6.50		
																	6.75		
																	7.00		
																	7.25		
																	7.50		
																	7.75		
																	8.00		
																	8.25		
																	8.50		
																	8.75		
																	9.00		
																	9.25		
																	9.50		
																	9.75		
																	10.00		
																	10.25		
																	10.50		
																	10.75		
																	11.00		
																	11.25		
																	11.50		
																	11.75		
																	12.00		
																	12.25		
																	12.50		
																	12.75		
																	13.00		
																	13.50		
																	14.00		
																	14.50		
																	15.00		

适用于Apply to	本产品
中心厚度公差C.T. Tolerance	+0.2mm-0.1mm不能低于1.0mm
边缘厚度公差E.T. Tolerance	±0.2mm
直径公差Diameter Tolerance	+0.2mm-0.4mm
设计DESIGN	非球
材料折射率MATERIAL INDEX	1.738
阿贝数ABBE VALUE	33.0
比重SPECIFIC GRAVITY	
透射比分类	0类, UV-1
变色性能	N/A

编写人/日期 WRITTEN BY / DATE	审核人/日期 VERIFIED BY / DATE	批准人/日期 APPROVED BY / DATE