



1.60 亚克力UV410非球面镜片参数表
1.60 Acrylic UV410 ASP LENS

编号: SWPS-FSV-069 版本: 1

前弯	后弯	中心厚度	边缘厚度	球光 (-/+)	前弯	后弯	中心厚度	边缘厚度
FRONT CURVE	BACK CURVE	CT (mm)	ET (mm)	SPH (-/+)	FRONT CURVE	BACK CURVE	CT (mm)	ET (mm)
4.00	4.00	2.1	2.2	0.00				
3.75	4.00	1.9	2.2	0.25				
3.50	4.00	1.8	2.4	0.50				
3.25	4.00	1.7	2.7	0.75				
3.00	4.00	1.6	2.8	1.00				
2.75	4.00	1.5	3.0	1.25				
2.50	4.00	1.4	3.3	1.50				
2.25	4.00	1.3	3.3	1.75				
2.00	4.00	1.2	3.5	2.00				
1.75	4.00	1.2	3.9	2.25				
1.50	4.00	1.2	4.3	2.50				
1.25	4.00	1.2	4.4	2.75				
1.00	4.00	1.2	4.7	3.00				
1.25	4.50	1.2	5.0	3.25				
1.00	4.50	1.2	5.3	3.50				
0.75	4.50	1.2	5.5	3.75				
0.50	4.50	1.2	5.8	4.00				
0.75	5.00	1.2	6.1	4.25				
0.50	5.00	1.2	6.4	4.50				
0.25	5.00	1.2	6.6	4.75				
0.00	5.00	1.2	6.8	5.00				
0.25	5.50	1.2	7.2	5.25				
0.00	5.50	1.2	7.5	5.50				
0.25	6.00	1.2	8.0	5.75				
0.00	6.00	1.2	8.2	6.00				
0.75	7.00	1.2	7.7	6.25				
0.50	7.00	1.2	7.9	6.50				
0.25	7.00	1.2	8.2	6.75				
0.00	7.00	1.2	8.4	7.00				
1.25	8.50	1.2	9.0	7.25				
1.00	8.50	1.2	9.2	7.50				
0.75	8.50	1.2	9.5	7.75				
0.50	8.50	1.2	9.7	8.00				
1.25	9.50	1.2	10.3	8.25				
1.00	9.50	1.2	10.4	8.50				
0.75	9.50	1.2	10.9	8.75				
0.50	9.50	1.2	11.2	9.00				
1.25	10.50	1.2	11.7	9.25				
1.00	10.50	1.2	11.8	9.50				
0.75	10.50	1.2	12.1	9.75				
0.50	10.50	1.2	12.3	10.00				

CYL(-)								SPH (-)
2.00	1.75	1.50	1.25	1.00	0.75	0.50	0.25	
								0.00
								0.25
								0.50
								0.75
								1.00
								1.25
								1.50
								1.75
								2.00
								2.25
								2.50
								2.75
								3.00
								3.25
								3.50
								3.75
								4.00
								4.25
								4.50
								4.75
								5.00
								5.25
								5.50
								5.75
								6.00
								6.25
								6.50
								6.75
								7.00
								7.25
								7.50
								7.75
								8.00
								8.25
								8.50
								8.75
								9.00
								9.25
								9.50
								9.75
								10.00

适用于Apply to	本产品
中心厚度允差C.T. Tolerance	-0.2mm +0.3mm (for CT 1.2) Other & PLUS; ± 0.3mm
边缘厚度允差E.T. Tolerance	±0.3mm
直径允差Diameter Tolerance	-0.5mm
设计DESIGN	非球面
材料折射率MATERIAL INDEX	1.598
阿贝数ABBE VALUE	32.0
比重SPECIFIC GRAVITY	1.26
透射比分类	0类, UV-1

编写人/日期 WRITTEN BY / DATE	审核人/日期 VERIFIED BY / DATE	批准人/日期 APPROVED BY / DATE