



1.60 UV410 球面镜片参数表

1.60 UV410 SPH LENS SPECIFICATION

编号: SWPS-FSV-070 版本: 1

前弯	后弯	中心厚度	边缘厚度	球光 (-/+)	前弯	后弯	中心厚度	边缘厚度
FRONT CURVE	BACK CURVE	CT (mm)	ET (mm)	SPH (-/+)	FRONT CURVE	BACK CURVE	CT (mm)	ET (mm)
4.50	4.50	1.9	1.9	0.00				
4.25	4.50	1.8	2.2	0.25	2.05	1.80	1.8	1.5
4.00	4.50	1.7	2.4	0.50	2.30	1.80	2.0	1.5
3.75	4.50	1.7	2.7	0.75	2.55	1.80	2.2	1.5
3.50	4.50	1.6	2.9	1.00	2.80	1.80	2.4	1.5
3.75	5.00	1.5	3.3	1.25	3.05	1.80	2.3	1.1
3.50	5.00	1.4	3.5	1.50	3.30	1.80	2.5	1.1
3.25	5.00	1.15	3.6	1.75	3.55	1.80	2.7	1.1
3.00	5.00	1.15	3.9	2.00	3.80	1.80	3.0	1.1
3.25	5.50	1.15	3.8	2.25	3.15	0.90	3.2	1.1
3.00	5.50	1.15	4.1	2.50	3.40	0.90	3.4	1.1
2.75	5.50	1.15	4.4	2.75	3.65	0.90	3.6	1.1
2.50	5.50	1.15	4.7	3.00	3.90	0.90	3.8	1.1
2.75	6.00	1.15	5.0	3.25	4.15	0.90	4.0	1.1
2.50	6.00	1.15	5.3	3.50	4.40	0.90	4.3	1.1
2.25	6.00	1.15	5.6	3.75	4.65	0.90	4.5	1.1
2.00	6.00	1.15	6.1	4.00	4.90	0.90	4.7	1.1
2.50	6.75	1.15	6.2	4.25	5.15	0.90	4.9	1.1
2.25	6.75	1.15	6.6	4.50	5.40	0.90	5.1	1.1
2.00	6.75	1.15	6.9	4.75	5.65	0.90	5.4	1.1
1.75	6.75	1.15	7.3	5.00	5.90	0.90	5.6	1.1
2.00	7.25	1.15	7.6	5.25	6.15	0.90	5.8	1.1
1.75	7.25	1.15	7.9	5.50	6.40	0.90	6.0	1.1
1.50	7.25	1.15	8.2	5.75	6.65	0.90	6.2	1.1
1.25	7.25	1.15	8.5	6.00	6.90	0.90	6.4	1.1
2.15	8.40	1.15	8.0	6.25				
1.90	8.40	1.15	8.3	6.50				
1.65	8.40	1.15	8.5	6.75				
1.40	8.40	1.15	8.7	7.00				
1.15	8.40	1.15	9.1	7.25				
0.90	8.40	1.15	9.3	7.50				
1.90	9.65	1.15	9.9	7.75				
1.65	9.65	1.15	10.1	8.00				
1.40	9.65	1.15	10.4	8.25				
1.15	9.65	1.15	10.6	8.50				
0.90	9.65	1.15	11.0	8.75				
0.65	9.65	1.15	11.2	9.00				
1.50	10.75	1.15	11.5	9.25				
1.25	10.75	1.15	11.9	9.50				
1.00	10.75	1.15	12.2	9.75				
0.75	10.75	1.15	12.5	10.00				

CYL(-)											SPH (-/+)	CYL(-)																
4.00	3.75	3.50	3.25	3.00	2.75	2.50	2.25	2.00	1.75	1.50		1.25	1.00	0.75	0.50	0.25	0.00	0.00	0.25	0.50	0.75	1.00	1.25	1.50	1.75	2.00		
																	0.00											
																	0.25											
																	0.50											
																	0.75											
																	1.00											
																	1.25											
																	1.50											
																	1.75											
																	2.00											
																	2.25											
																	2.50											
																	2.75											
																	3.00											
																	3.25											
																	3.50											
																	3.75											
																	4.00											
																	4.25											
																	4.50											
																	4.75											
																	5.00											
																	5.25											
																	5.50											
																	5.75											
																	6.00											
																	6.25											
																	6.50											
																	6.75											
																	7.00											
																	7.25											
																	7.50											
																	7.75											
																	8.00											
																	8.25											
																	8.50											
																	8.75											
																	9.00											
																	9.25											
																	9.50											
																	9.75											
																	10.00											

适用于Apply to	本产品
中心厚度允差C.T. Tolerance	- 0.15mm +0.2mm (for CT 1.15) Other & PLUS ; ± 0.2mm
边缘厚度允差E.T. Tolerance	± 0.3mm
直径允差Diameter Tolerance	-0.5mm
设计DESIGN	球面
材料折射率MATERIAL INDEX	1.597
阿贝数ABBE VALUE	40.0
比重SPECIFIC GRAVITY	1.28
透射比分类	0类, UV-1

编写人/日期 WRITTEN BY / DATE	审核人/日期 VERIFIED BY /DATE	批准人/日期 APPROVED BY /DATE