



1.67 2号UV防蓝光双面非球面镜片参数表

1.67 BLUE PRO DOUBLE ASPHERIC LENS SPECIFICATION

编号: SWPS-FSV-075 版本: 1

[返回](#)

前弯	后弯	中心厚度	边缘厚度	球光 (-/+)	前弯	后弯	中心厚度	边缘厚度
FRONT CURVE	BACK CURVE	CT (mm)	ET (mm)	SPH (-/+)	FRONT CURVE	BACK CURVE	CT (mm)	ET (mm)
2.50	4.50	1.15	3.1	2.00				
2.75	5.00	1.15	3.3	2.25				
2.50	5.00	1.15	3.6	2.50				
2.25	5.00	1.15	3.7	2.75				
2.00	5.00	1.15	4.0	3.00				
2.25	5.50	1.15	4.3	3.25				
2.00	5.50	1.15	4.5	3.50				
1.75	5.50	1.15	4.6	3.75				
1.50	5.50	1.15	4.9	4.00				
1.75	6.00	1.15	5.3	4.25				
1.50	6.00	1.15	5.6	4.50				
1.25	6.00	1.15	5.7	4.75				
1.00	6.00	1.15	5.9	5.00				
1.25	6.50	1.15	6.3	5.25				
1.00	6.50	1.15	6.5	5.50				
0.75	6.50	1.15	6.7	5.75				
0.50	6.50	1.15	6.8	6.00				
1.00	7.25	1.15	6.7	6.25				
0.75	7.25	1.15	6.9	6.50				
0.50	7.25	1.15	7.3	6.75				
0.25	7.25	1.15	7.8	7.00				
1.00	8.25	1.15	7.9	7.25				
0.75	8.25	1.15	8.0	7.50				
0.50	8.25	1.15	8.3	7.75				
0.25	8.25	1.15	8.5	8.00				
1.00	9.25	1.15	8.8	8.25				
0.75	9.25	1.15	9.0	8.50				
0.50	9.25	1.15	9.3	8.75				
0.25	9.25	1.15	9.5	9.00				
1.00	10.25	1.15	9.8	9.25				
0.75	10.25	1.15	10.2	9.50				
0.50	10.25	1.15	10.5	9.75				
0.25	10.25	1.15	10.7	10.00				

2.00	1.75	1.50	1.25	1.00	0.75	0.50	0.00	SPH (-)
								2.00
								2.25
								2.50
								2.75
								3.00
								3.25
								3.50
								3.75
								4.00
								4.25
								4.50
								4.75
								5.00
								5.25
								5.50
								5.75
								6.00
								6.25
								6.50
								6.75
								7.00
								7.25
								7.50
								7.75
								8.00
								8.25
								8.50
								8.75
								9.00
								9.25
								9.50
								9.75
								10.00

适用于 Apply to	本产品
中心厚度允差 C.T. Tolerance	-0.15mm +0.2mm
边缘厚度允差 E.T. Tolerance	±0.3mm
直径允差 Diameter Tolerance	-0.5mm
设计 DESIGN	非球面
材料折射率 MATERIAL INDEX	1.665
阿贝数 ABBE VALUE	32.0
比重 SPECIFIC GRAVITY	1.34
透射比分类	0类, UV-1

编写人/日期 WRITTEN BY / DATE	审核人/日期 VERIFIED BY / DATE	批准人/日期 APPROVED BY / DATE