



视悦变1.56灰变非球面克拉膜

FSV 1.56 UV400 ASP SPIN COATING GREY FRONT LIGHT BLUE BACK LIGHT GREEN+ANTI-SCRATCH COATING SHMC

编号: SWPS-FSV-077 版本: 1

前弯	后弯	中心厚度	边缘厚度	球光 (-/+)	前弯	后弯	中心厚度	边缘厚度
FRONT CURVE	BACK CURVE	CT (mm)	ET (mm)	SPH (-/+)	FRONT CURVE	BACK CURVE	CT (mm)	ET (mm)
3.00	3.00	2.0	2.2	0.00				
2.75	3.00	1.9	2.3	0.25	3.25	3.00	1.8	1.6
2.50	3.00	1.8	2.5	0.50	3.50	3.00	2.1	1.6
2.25	3.00	1.7	2.7	0.75	3.75	3.00	2.0	1.6
2.00	3.00	1.6	2.9	1.00	4.00	3.00	2.3	1.6
1.75	3.00	1.5	3.1	1.25	4.25	3.00	2.4	1.4
3.00	4.50	1.4	3.2	1.50	4.50	3.00	2.7	1.4
2.75	4.50	1.2	3.3	1.75	4.75	3.00	2.8	1.4
2.50	4.50	1.2	3.7	2.00	5.00	3.00	3.2	1.4
2.25	4.50	1.2	4.0	2.25	4.25	2.00	3.1	1.2
2.00	4.50	1.2	4.3	2.50	4.50	2.00	3.3	1.2
1.75	4.50	1.2	4.6	2.75	4.75	2.00	3.7	1.2
1.50	4.50	1.2	5.0	3.00	5.00	2.00	4.0	1.2
1.25	4.50	1.2	5.2	3.25	5.25	2.00	4.1	1.2
1.00	4.50	1.2	5.5	3.50	5.50	2.00	4.3	1.2
0.75	4.50	1.2	5.8	3.75	5.75	2.00	4.6	1.2
0.50	4.50	1.2	6.1	4.00	6.00	2.00	4.7	1.2
1.25	5.50	1.2	6.4	4.25	5.25	1.00	4.9	1.2
1.00	5.50	1.2	6.7	4.50	5.50	1.00	5.2	1.2
0.75	5.50	1.2	6.9	4.75	5.75	1.00	5.4	1.2
0.50	5.50	1.2	7.2	5.00	6.00	1.00	5.7	1.2
1.25	6.50	1.2	7.6	5.25	6.25	1.00	5.9	1.2
1.00	6.50	1.2	8.1	5.50	6.50	1.00	6.1	1.2
0.75	6.50	1.2	8.3	5.75	6.75	1.00	6.4	1.2
0.50	6.50	1.2	8.6	6.00	7.00	1.00	6.6	1.2
1.25	7.50	1.2	8.6	6.25				
1.00	7.50	1.2	8.9	6.50				
0.75	7.50	1.2	9.3	6.75				
0.50	7.50	1.2	9.3	7.00				
1.25	8.50	1.2	10.1	7.25				
1.00	8.50	1.2	10.3	7.50				
0.75	8.50	1.2	10.6	7.75				
0.50	8.50	1.2	10.7	8.00				

CYL(-)								SPH (-/+)	CYL(-)									
2.00	1.75	1.50	1.25	1.00	0.75	0.50	0.25		0.00	0.00	0.25	0.50	0.75	1.00	1.25	1.50	1.75	2.00
								0.00										
								0.25										
								0.50										
								0.75										
								1.00										
								1.25										
								1.50										
								1.75										
								2.00										
								2.25										
								2.50										
								2.75										
								3.00										
								3.25										
								3.50										
								3.75										
								4.00										
								4.25										
								4.50										
								4.75										
								5.00										
								5.25										
								5.50										
								5.75										
								6.00										
								6.25										
								6.50										
								6.75										
								7.00										
								7.25										
								7.50										
								7.75										
								8.00										

适用于Apply to	uno400
中心厚度允差C.T. Tolerance	±0.3mm最低1.0mm
边缘厚度允差E.T. Tolerance	±0.3mm
直径允差Diameter Tolerance	-0.5mm
设计DESIGN	非球面
材料折射率MATERIAL INDEX	1.550
阿贝数ABBE VALUE	35.0
比重SPECIFIC GRAVITY	1.28
透射比分类	0类

编写人/日期 WRITTEN BY / DATE	审核人/日期 VERIFIED BY / DATE	批准人/日期 APPROVED BY / DATE